


TECHNICAL DATA

STABILIZERS/ RECYCLERS

RS 460, RS 500





Dimensions in mm

	A	B	H	H1	K	L
RS 460	6073	2872	3100	3885	510	9579
RS 500	6073	2530	3100	3885	510	9579

Shipping dimensions in m3

RS 460	85,284
RS 500	75,128

Technical Data

BOMAG RS 460

BOMAG RS 500

Weights

Operating weight CECE	kg	24.200	24.900
Axle load, front CECE	kg	16.050	16.030
Axle load, rear CECE	kg	8.150	8.870
Max. weight	kg	27.250	31.000

Driving Characteristics

Speed (1)	km/h	0- 3,0	0- 3,0
Speed (2)	km/h	0- 12,0	0- 12,0
Max. gradeability (dep. on soil con.)	%	40	40

Drive

Engine manufacturer		Merc.-Benz	Merc.-Benz
Engine type		OM 471 LA	OM 471 LA
Emission stage		Stage V / TIER4f	Stage V / TIER4f
Exhaust gas aftertreatment		DOC+DPF+SCR	DOC+DPF+SCR
Cooling		Liquid	Liquid
Number of cylinders		6	6
Performance ISO 9249	kW	340,0	390,0
Performance SAE J 1995	hp	456,0	523,0
Speed	min-1	1.600	1.600
Electric equipment	V	24	24
Drive system		hydrost.	hydrost.
Driven wheels		all wheel	AWD 4x4

Tyres

Tyre size, front	24.5-32 24PR	24.5-32 24PR
Tyre size, rear	23.1-26 20PR	23.1-26 20PR

Brakes

Service brake	hydrost.	hydrost.
Parking brake	multi disc	multi disc

Steering

Steering system	Art. + rear	Art. + rear
Steering method	hydraulic	hydraulic

Rotor

Rotor width	mm	2.440	2.250
Rotor diameter, outer	mm	1.224	1.224
Rotor speed	min-1	104- 179	100- 180
Rotor oscillation angle +/-	grad	8	8
Sense of rotation		up-cut	up-cut
Max. cutting depth	mm	500	500
Number of cutting teeth		160	160
Height of cutting teeth	mm	290	240

Capacities

Fuel	l	875,0	875,0
Water	l	850,0	850,0
AdBlue (DEF) ®	l	85,0	85,0

Technical modifications reserved. Machines may be shown with options.

Standard Equipment

- ☒ Hydrostatic drive / all wheel
- ☒ Anti Slip Control (ASC) (RS460)
- ☒ Hydr./ mech. rotor drive with autom. power control
- ☒ Rotor laterally slidable (RS500)
- ☒ Hydr. adjustable rotor inclination, automatic
- ☒ BOMAG FLEXMIX Technology (RS500)
- ☒ Universal rotor with exchange holder BMS15
- ☒ Hydr. tailgate with floating position+Load application function
- ☒ Hydrostatic articulated steering
- ☒ Hydrostatic rear axle steering
- ☒ 4 Steering modes
- ☒ Height adjustable ROPS cab
 - Transport/working position
 - slewable/slidable multi-function work place
 - heating
 - Air condition
 - Radio
- ☒ Working lights (LED)
- ☒ Rotary beacon
- ☒ Camera system Plus
- ☒ 4x Emergency STOP
- ☒ Air compressor + Connecting port for compressed air tools
- ☒ Lockable stowage compartments
- ☒ Central lubrication system (RS500)
- ☒ Rotary unit for rotor forward/reverse
- ☒ Pneumatic hammer for changing cutting tools
- ☒ compressed air system + Compressed air set

Optional Equipment

- ☐ Water metering system (900l + 1600l)
- ☐ Water prefilter
- ☐ Emulsion metering system 900l/min.
- ☐ Emulsion pre-filter for water system
- ☐ Dosing bar for cement suspension
- ☐ Printer for metering computer
- ☐ Quick-change holder 20mm (BMS15)
- ☐ High pressure cleaner
- ☐ Central lubrication system (RS460)
- ☐ Tool kit
- ☐ Quick refuelling system
- ☐ BOMAG TELEMATIC POWER
- ☐ Special painting
- ☐ Biodegradable hydraulic oil
- ☐ Widening of Track, front (RS500)
Overall width: 2.800mm
- ☐ Vibratory plate (RS460)

